



# PL2

HEAVY DUTY

PL2 GREASE

PL2 grease is designed to provide wear and corrosion protection for bearings, roll necks, spindles and other grease lubricating parts operating at elevated temperatures and applications of extreme water exposure. PL2 resists consistency breakdown from water, coolant, or process fluid contamination and virtually eliminates grease run out.

**01.**  
**Steel Mill**



**02.**  
**Conveyor**



**03.**  
**Mining**



**04.**  
**Dragline Boom**



**01 Product Description (Benefits)**

- Exceptional resistance to water, provides consistent lubrication even in harsh weather and inherent protection from rust and corrosion
- Mechanically stable, virtually no consistency change during/ after usage
- Wide service temperature (-20°C ~ 232°C / -5°F ~ 450°F)
- Mineral oil + Calcium Sulfonate, Gray

**02 Application Part**

- Automatic grease lubricator
- Shovels, drag lines, haul trucks, and conveyors
- Drills, rock crushers, and mills

**03 Product Data**

| Test item                         | Result    |
|-----------------------------------|-----------|
| NLGI # Grade                      | 1         |
| Base Oil Viscosity, 40°C          | 220       |
| Worked Penetration                | 310 ~ 340 |
| Dropping Point                    | > 315     |
| Water Washout                     | < 1       |
| 4Ball Extreme Pressure Properties | < 800     |
| % Moly                            | 5.0       |

Note : The above data constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field test with the product selected for a specific application

**04 Suggestion of Using**

Spatula, brush, lever grease guns and automatic lubricating systems

※ Storage : Recommend using within a year if the product is stored in the original closed container in a dry place

